

Yamaha 9.9/15FMH Every 100 hour or Annual service

Procedure

Fuel tank & hose - check for leaks & damage
 Cowling clamp - inspect & lubricate yearly.
 Fuel line - inspect for leaks and deterioration.
 Fuel filter - clean
 Carburettor - check for leakage, check idle rpm
 Spark plugs - replace
 Exhaust cover - torque bolts to 12Nm.
 Flywheel nut - torque to 105Nm.
 Water leakage - inspect for water leaks
 Motor exterior - inspect for abnormalities.
 Exhaust leakage - inspect for leaks
 Cooling water passage - inspect & clean where required
 Ignition timing - inspect, adjust if required
 Throttle link - inspect, adjust if required
 Throttle cable - inspect, adjust where required
 Start in gear protection - test, adjust if required
 Gear oil - drain, check for water, inspect & refill
 Propeller - remove, check for damage, inspect propeller shaft,
 lubricate shaft, refit propeller.
 Water pump - remove lower unit, inspect water pump, replace
 where required, grease drive shaft (WR2 grease), refit lower unit, check gear travel.
 Annodes - inspect, replace where required
 Wiring & connections - inspect, repair / replace where required
 Thermostat - check operation against specifications.
 Bolts & nuts - inspect, tighten where loose.
 Grease points - lubricate, Tilt Tube, Swivel Bracket, with water proof grease.
 Clean & degrease.

includes

br7hs-10	2
leg oil 1=100ml	2.5
labour	2.4
lube	1
leg gasket	2

Cost

\$ 265